

All assembled pumps are tested to verify hydraulic, mechanical and electrical performance prior to shipment.

Standard delivery is one week.

1750 RPM

SP



Please visit www.ampcopumps.com for individual pump curves and dimensional drawings.

MANUFACTURED, ASSEMBLED AND TESTED IN GLENDALE, WISCONSIN

Ampco Pumps Company

Ampco Pumps Company 2045 W. Mill Road Glendale, WI 53209 Phone: 800-737-8671 Email: sales@ampcopumps.com

Ampco Pumps GmbH Am Gäxwald 6 76863 Herxheim Germany Phone: +49 7276 5058515 Email: info@ampcopumps.de



Ampco Pumps Company

• With front-loading seal design



www.AmpcoPumps.com

f in



LC/LD/LF/SP SERIES PUMPS

LC/LD/LF

Ampco now offers three lines of high efficiency centrifugal pumps to meet all sanitary requirements.

- LF pumps offer a front-loading seal design for ease of maintenance and are easily convertible to a double seal without changing any other parts.
- High efficiency design and performance offers gentle product handling capability up to 1200 cps.
- Heavy-wall construction, tight manufacturing tolerances, dynamically balanced impellers and a self-aligning shaft minimize vibration and promote longer seal life.
- Standard adapters are made of 304 SS to resist corrosion.



Ampco pumps are dimensionally	Ampco Series	Competing Series
and hydraulically	LC	FPX
interchangeable	LD	FP
with competing	LF	FPR
brands.	SP	FZX

Standard Material:

LC SINGLE SEAL

• Optional chrome oxide rotating element

• Silicon carbide / Carbon / Viton

TYPICAL APPLICATIONS

- Beverages: Fruit juices, fruit concentrate, mash, high fructose corn syrup, liquor, wine, beer, wort, yeast
- **Candy:** Corn syrup, chocolate, sugar solutions
- **CIP:** Caustics, enzyme cleaners, solutions
- **Cosmetics:** Lotions, soaps, shampoo
- **Dairy:** Cream, ice cream, buttermilk, milk, whey
- **Oils:** Salad, frying, cooking
- Personal Care: Cologne, mouthwash
- **Pharmaceuticals & Biotech**


• Tight manufacturing tolerances and the unique vane-shaped impeller enable SP pumps to handle shear sensitive products efficiently. • SP pumps are available with either single or double external mechanical seals.

JAV 3

• Standard adapters are made of 304 SS to resist corrosion.


STANDARD SEAL OPTIONS

LD DOUBLE SEAL Standard Material: • Silicon carbide / Carbon / Ceramic / Viton Optional chrome oxide rotating element



LF SINGLE SEAL

Standard Material: • Silicon carbide / Carbon / Viton Optional double seal





handling products with entrained air.



The self-priming capability of Ampco's SP liquid ring pumps make them ideally suited for CIP return applications and for

> • The ability to handle products with entrained air makes SP pumps extremely efficient for emptying tanks and drums.

