# AMPCO'S WINE AND MUST CART

Featuring Ampco's ZP1 Series pump



- · Wine/Juice Transfer
- · Barrel Work
- · Filter Feed
- · Bottling/Filler Supply





### **Standard Pump Features:**

- 316L stainless steel wetted parts with Alloy 88 non-galling rotors
- 304 stainless steel gearcase
- Single o-ring seals
- Tri-clamp connections
- Bearing protection package
- High efficiency TEFC motors with 20:1 turndown ratio

## **Common Pump and Motor Options:**

- Single and double mechanical seals
- Multiple connection options
- Washdown and stainless steel motor enclosures
- NEMA or IEC motor frames

#### **Control Features:**

- NEMA 4X VFD
- Remote speed potentiometer
- Membrane control with digital display
- Washdown approved wiring, cord and plug options are available upon request

#### Cart Features:

- 304 stainless steel construction
- 10" foam filled tires with greaseable roller bearings

Model	Inlet / Outlet size	Motor	Flow / Max	Pressure / Max
WC-30	1.5"	2 HP / 1.5 kW	30 gpm / 7 m <sup>3</sup> /h	60 psi / 4 bar
WC-40	2"	3 HP / 2.2 kW	40 gpm / 9 m³/h	60 psi / 4 bar
WC-60	2.5"	5 HP / 4 kW	70 gpm / 16 m³/h	80 psi / 5.5 bar
WC-130	3"	7.5 HP / 5.5 kW	135 gpm / 31 m³/h	80 psi / 5.5 bar

Contact Ampco's technical sales team for additional options. sales@ampcopumps.com / 800.737.8671

Ampco Pumps Company 2045 W. Mill Road Glendale, WI 53209 Phone: 800.737.8671 sales@ampcopumps.com



Ampco Pumps GmbH Gewerbepark West II 7 76863 Herxheim Germany Phone: +49 7276 5058515 info@ampcopumps.de

## AMPCO'S CELLAR CART FOR BEER & CIP

Ampco's Cellar Cart for beer and CIP is a lightweight, robust two-wheeled cart designed for maximum mobility. Constructed of stainless steel tubing, the Cellar Cart has solid polypropylene wheels and is corrosion resistant. Each versatile cart is built to customer specifications and can include any of Ampco's centrifugal pumps, positive displacement pumps, or blenders. Carts are ergonomically designed for ease of use in tight spaces.







Model CB180 / AC+ 216 with NEMA 4X VFD. Shown with a wash-down 5 HP 3500 RPM motor.

Model CB56 / AC+ 114 with NEMA 4X VFD. Shown with a stainless steel 1.5 HP 3500 RPM motor.

Ampco Pumps Company 2045 W. Mill Road Glendale, WI 53209 Phone: 800.737.8671 sales@ampcopumps.com Ampco Pumps Company
www.ampcopumps.com

**3** 

Ampco Pumps GmbH Gewerbepark West II 7 76863 Herxheim Germany Phone: +49 7276 5058515 info@ampcopumps.de